






Inserti - *Inserts*

KN	Materiale <i>Material</i>	Acciaio - Steel	P														
		Acciaio inox - Stainless steel	M														
		Ghisa - Cast iron	K														
		Leghe leggere - Aluminium alloys	N														
		Resistenti al calore - Heat resistant	S														
		Materiali temprati - Hardened material	H														
	Codice di ordinazione <i>Ordering code</i>	Dimensioni - Size					HC Ricoperti - Coated							HW Non Ricoperti Uncoated			
		l	d	s	d ₁	r	CT9325	PT4320	PT4730	PT8130	CT4125			WT1010			
	KNUX 160405-L11	16.00	9.52	4.76	-	0.5					•						
	KNUX 160410-L11	16.00	9.52	4.76	-	1.0					•						
	KNUX 160405-R11	16.00	9.52	4.76	-	0.5					•						
	KNUX 160410-R11	16.00	9.52	4.76	-	1.0					•						

RC	Materiale <i>Material</i>	Acciaio - Steel	P	■													
		Acciaio inox - Stainless steel	M	■										■			
		Ghisa - Cast iron	K	■	■									■			
		Leghe leggere - Aluminium alloys	N		■									■			
		Resistenti al calore - Heat resistant	S	■										■			
		Materiali temprati - Hardened material	H														
	Codice di ordinazione <i>Ordering code</i>	Dimensioni - Size					HC Ricoperti - Coated							HW Non Ricoperti Uncoated			
		l	d	s	d ₁	r	CT9325	PT4320	PT4730	PT8130				WT1010			
	RCGT 0803MO-CA	-	8.00	3.18	3.40	-								•			
	RCGT 1003MO-CA	-	10.00	3.18	4.00	-								•			
	RCMT 0602MO-CM	-	6.00	2.38	2.80	-	•	•									
	RCMT 0803MO-CM	-	8.00	3.18	3.40	-	•	•									
	RCMT 1003MO-CM	-	10.00	3.18	4.00	-	•	•									
	RCMT 1204MO-CM	-	12.00	4.76	4.20	-	•	•									

■ Applicazione Consigliata
Recommended Application

▣ Applicazione Possibile
Possible Application

• Disponibile
In stock

○ A richiesta
On request